

## Wellman

### volteador de paquetes

Volteador de bultos remoto, usado de calidad.

### Especificaciones técnicas

CazProductNumber EMPRESA	5478
Nombre	Wellman
Longitud max de hoja	700 mm
Ancho max de hoja	1100 mm

### Videos

No hay vídeos disponibles para este producto.

### Fotos





68-16018  
**WELLMAN CONTROLLED HEAT & AIR DIVISION**

### LUBRICATION RECOMMENDATIONS

LOCATION	METHOD	LUBRICANT		PERIOD
		SHELL	BP	
CONVEYOR CHAIN	MIST SPRAY	CARNEA OIL 15 plus 2% Graphite	ENERGOL EM 35 plus 2% Graphite	CONTINUOUS SPRAY
FAN BEARINGS BELOW 130°C	GREASE NIPPLES	ALVANIA GREASE 3	ENERGREASE LS 3	WEEKLY
130°C - 200°C	GREASE NIPPLES	DARINA GREASE R2	ENERGREASE HTB 2	WEEKLY
200°C - 600°C	GREASE NIPPLES	ET GREASE	—	WEEKLY
MOTOR BEARINGS	GREASE NIPPLES	ALVANIA GREASE 3	ENERGREASE LS 3	ANNUALLY
CONVEYOR BEARINGS BELOW 200°C	GREASE NIPPLES	DARINA GREASE R2	ENERGREASE HTB 2	WEEKLY
OVER 200°C	GREASE NIPPLES	ET GREASE	—	WEEKLY
CHAIN DRIVES	HAND OILED	VALVATA OIL 79	ENERGOL CS 425	WEEKLY
DOOR CHAINS	HAND OILED	VALVATA OIL 79	ENERGOL CS 425	WEEKLY
GEARBOX	OIL FILLED	VALVATA OIL 79	ENERGOL CS 425	INSPECT WEEKLY
VARIABLE SPEED GEAR	OIL FILLED	VALVATA OIL 79	ENERGOL CS 425	INSPECT WEEKLY
MITRE BOX	OIL FILLED	VALVATA OIL 79	ENERGOL CS 425	INSPECT WEEKLY

WEEKLY - EVERY 40 WORKING HOURS  
CORNWALL ROAD, SMETHWICK, WARLEY, WORCESTERSHIRE.

